

Selection guide

Application	Type												
	DF11	DF21	DF22	DF23	DF24	DF25	DF26	DF27	DF28	DF29	DF30	DF31	DF33
Full indicator	X	X	X	X	X	X	X	X	X	X	X	X	X
Demand indicator	X	X	X	X	X	X	X	X	X	X		X	X
Empty indicator	X	X	X	X	X	X	X	X	X	X		X	X
Any mounting position	X	X	X	X	X				with KD			X	X
Horizontal mounting	X	X	X	X	X	X			with KD		X	X	X
Lateral mounting	X	X	X	X	X	X			with KD			X	X
Vertical from top	X	X	X	X	X		X	X	X	X	X	X	X
Inclined from top	X	X	X	X	X				with KD			X	X
Inclined from bottom	X	X	X	X	X				with KD			X	X
Loading set	X	X		X							X		
Height adjustable									X				
For moist bulk goods	X	X	X	X	X	X	X	X	X	X	X	X	X
For wet bulk goods												X	X
Vertical from top and immersion in liquids	X						X	X	X	X			X
Lateral below the liquid level												X	X
Demand indicator for soluble bulk goods in liquids												X	X
Recognize by touch of bulk goods in liquids							X	X	X	X		X	X
For sludges vertical from top							X	X	X	X		X	X
In moist and aggressive gases		X	X	X	X	X	X	X	X	X	X	X	X
In moist gases with high temperatures												X	X
Temperatures up to 260°C		X	X	X	X	X	X	X	X	X		X	
Temperatures up to 500°C		X	X				X	X	X	X		350°C	
Temperatures up to 1000°C		X	X				X	X	X	X			

Caution! Level indicator is always to be brought into circuit so that no undesirable switching function can occur in the case of mains voltage failure.